



Designación	M kg/m	P kN/m	h mm	b mm	t _w mm	t _f mm
HEM 100	41,8	0,418	120	106	12,0	20,0
HEM 120	52,1	0,521	140	126	12,5	21,0
HEM 140	63,2	0,632	160	146	13,0	22,0
HEM 160	76,2	0,762	180	166	14,0	23,0
HEM 180	88,9	0,889	200	186	14,5	24,0
HEM 200	103,1	1,031	220	206	15,0	25,0
HEM 220	117,3	1,173	240	226	15,5	26,0
HEM 240	156,7	1,567	270	248	18,0	32,0
HEM 260	182,4	1,824	290	268	18,0	32,5
HEM 280	188,5	1,885	310	288	18,5	33,0
HEM 300	237,9	2,379	340	310	21,0	39,0
HEM 320	245,0	2,45	359	309	21,0	40,0
HEM 340	247,9	2,479	377	309	21,0	40,0
HEM 360	250,3	2,503	395	308	21,0	40,0
HEM 400	255,7	2,557	432	307	21,0	40,0
HEM 450	263,3	2,633	478	307	21,0	40,0
HEM 500	270,3	2,703	524	306	21,0	40,0
HEM 550	278,2	2,782	572	306	21,0	40,0
HEM 600	285,5	2,855	620	305	21,0	40,0